



# Bolt Tension Stabilization


Patented

# Fcon<sup>®</sup>

®



## New Bolt-Tension Stabilizing Method

*By applying high performance liquefied polymer "Fcon" to the threaded part of the bolt, the variation in axial tension is limited to within 10% when tightening with a torque wrench.*



Obtain  
**Stable**  
Axial Tension





## Features

- Offers the highest level of tension stabilization in the world.
- Reduces temperature-related fluctuations in tension.
- Optimal tension repeatability demonstrated by repeated tightening.
- Superior loosening characteristics compared to machine oil.

## Applications

Fcon stabilizing method is effective for the safety, reliability, and preservation of parts secured with bolts. The main application for Fcon is the bolting of critical parts to insure the preservation of assemblies on bridges, railroads, cars, construction machinery and airplanes. Ideal for plant maintenance, repair, and inspection.

## Specifications

- Individual bottle size: Net Wt. 90g
- Sold in cases of ten bottles
- One bottle lubricates approx. 300 M10 size bolts
- Polymeric hydrocarbon based product
- Non hazardous to man and environment

*Contact Tohnichi Staff for more details and samples!*

### N.V. TOHNICHI EUROPE S.A.

Industrieweg 27 Boortmeerbeek, B-3190  
BELGIUM  
TEL. 32 16 60 66 61  
FAX. 32 16 60 66 75  
E-mail : tohnichi-europe@online.be

### TOHNICHI MFG.CO.,LTD.

2-12, Omori-kita, 2-Chome Ota-ku,  
Tokyo, JAPAN  
TEL. 81 3 3762 2455  
FAX. 81 3 3761 3852  
E-mail : overseas@tohnichi.co.jp  
WebSite : <http://www.tohnichi.co.jp>

### TOHNICHI AMERICA CORP.

677 Academy Drive, Northbrook,  
Illinois 60062, U.S.A.  
TEL. 1 847 272 8480  
FAX. 1 847 272 8714  
E-mail : [inquiry@tohnichi.com](mailto:inquiry@tohnichi.com)  
WebSite : <http://www.tohnichi.com>

